




The MP2000/2000/300K-A is suitable for broadband low noise and linear power amplification. The amplifier employs E-pHEMT technology that provides wide dynamic range, low noise figure, excellent linearity and unconditional stability.



Model: MP1250/2000/300K-A

1. Electrical Characteristics

Item	Value	Note
Frequency Range	500 ~ 2000 MHz	
Gain	30 dB (Typ.)	
Gain Flatness	± 1.0 dB (Max.)	Over Freq. Range
Gain Variation	± 0.5 dB	Over Temp. Range
Output P1	+20 dBm (Min.)	
Input / Output VSWR	2.0:1 (Max.)	
Noise Figure	2.0 dB (Max.)	@ 25 °C
Output 3 rd Intercept	+36 dBm (Typ.)	Two tones, @ +7 dBm per tone, 1 MHz spacing
Spurious	-70 dBc (Max.)	
DC Input	+ 15V / 0.32A (Typ.)	
Input / Output Impedance	50 Ω	
Max Input Power	+5 dBm	

2. Mechanical Characteristics

RF IN/OUT	SMA Female	4 – 40 screw
DC Input	#8 Feed-thru	
Dimensions	2.1" x 1.85" x 0.62"	

3. Environment Characteristics

Operating Temperature	-20°C ~ +80°C	Base Plate
-----------------------	---------------	------------

Revision History

REV	Reason to Change	Date	Initialed by

4. Outline Drawing

