



The MP900/200/40SK-A2 is suitable for broadband high power linear applications. The amplifier employs linear LDMOS power devices that provide sufficient output power, wide dynamic range, and high gain.

Amplifier is equipped with internal Automatic Level Control loop, enabling it to be set to an Output Power level with maximal linearity at specific Communication System component environment.

Model: MP900/200/40SK-A2

1. Electrical Characteristics		
Item	Value	Note
Frequency Range	800 ~ 1000 MHz	
Gain	50 ± 1dB	
Gain Flatness	ALC Off	Over Freq. Range 100 MHz Bands
	ALC On	
	±1.0 dB (Max.)	±0.5 dB (Max.)
Gain Variation	± 1dB	Over Temp. Range
Output Power P1	+42 dBm (Typ.)	
Output Power Psat	+ 43 dBm (Min.)	
Output 3 rd Intercept Point	+ 57 dBm	2 tones @ +36 dBm output power, 1 MHz Spacing
Input / Output VSWR	≤ 1.2	Output Isolator Included
Harmonics	-45 dBc (Max.)	@ P1 dB
Spurious	-70 dBc (Max.)	
HPA Enable/Disable	TTL "0V or Open" ⇒ Enable TTL "5V" ⇒ Disable	
ALC ON/OFF	TTL "0V or Open" ⇒ ON TTL "5V" ⇒ OFF	Via Pin 3 on DB-9
ALC Level	ALC Setting Range >15 dB	Continuous Adjust. via Pin 4 on DB-9
Forward Power Monitor	4.0 ± 0.1 V @ +40 dBm	RMS Detection
Reverse Power Monitor	4.0 ± 0.1 V @ +40 dBm	RMS Detection
DC Input Voltage	+28 VDC	
DC Input Current	1.7 A (Max.)	Pout @ +40 dBm
Thermal Shutdown	+85 °C ± 5 °C	Auto Recover @ +70 °C ± 5 °C
Input / Output Impedance	50 Ω	
Max. Input without Damage	+0 dBm	With ALC on

2. Mechanical Characteristics		
Monitoring Connector	DB-9 Male	4 – 40 screw
RF IN/OUT Connector	SMA 4 Holes – Female	
DC Input	Pin 6,7 on DB9	
Dimensions	5.92" x 2.98" x 1"	
LED	LED Indicator	ALC On

Revision History			
REV	Reason to Change	Date	Initialed by

3. Environment Characteristics		
Operating Temperature	-20 °C ~ +70 °C	Base Plate
Cooling	External Heat-sink	
Humidity (Non-condensing)	95% (Max.)	

4. DB9 Pin Description		
1	Forward Power Monitor	
2	Reverse Power Monitor	
3	ALC ON/OFF	
4	ALC Level Input	0 – 5V
5	Enable / Disable	Enable: TTL Low or Open Disable: TTL High
6, 7	28V	
8	ALC On Indicator	ALC on +5V
9	Ground	

5. Outline Drawing

