



The MP900/300/300K-A is suitable for broadband low noise and linear power amplification. The amplifier employs GaAs E-pHEMT technology that provides wide dynamic range, low noise figure, excellent linearity and unconditional stability.



Model: MP900/300/300K-A

1. Electrical Characteristics		
Item	Value	Note
Frequency Range	700 ~ 1000 MHz	
Gain	30dB (Typ.)	
Gain Flatness	±1.0 dB	Over Freq. Range
Gain Variation	±1.0 dB	Over Temp. Range
Output P1	+28 dBm (Min.)	
Input / Output VSWR	1.3:1 (Max.)	
Noise Figure	1.0 dB (Max.)	
Output 3 rd Intercept	+42 dBm (Typ.)	Two tones, +17 dBm per tone, 1 MHz spacing
Spurious	-70 dBc (Max.)	
DC Input	8 - 12V / 0.50A (Typ.)	
Input / Output Impedance	50 Ω	
Max Input Power	+2 dBm	

2. Mechanical Characteristics		
RF IN/OUT	DB-9-Male	4 – 40 screw
DC Input	SMA 4 Holes – Female	
Dimensions	2.1 x 1.85 x 0.62	

3. Environment Characteristics		
Operating Temperature	-20°C ~ +70°C	Base Plate

4. Outline Drawing

