




The MP750/500/46MK-A10T is suitable for 500 - 1000 MHz high power linear applications. The amplifier employs linear LDMOS power devices that provide sufficient output power, wide dynamic range, and high gain.

Model: MP750/500/46MK-A10T

1. Electrical Characteristics		
Item	Value	Note
Frequency Range	500 ~ 1000 MHz	
Gain	40 dB (Min.) 45 dB (Max.)	
Gain Flatness	± 1.0 dB	Over Freq. Range
Gain Flatness in Load Condition 3:1	± 3.0 dB (Typ.)	Tested with 3 dB attenuator Open Port
Gain Variation	± 1 dB	Over Temp. Range
Output Power Psat	+46 dBm (Min.)	
IP3	+52 dBm (Min.)	Two Tones @ +40 dBm per tone 12.5 KHz Spacing
Input / Output VSWR	≤ 1.5	
Harmonics	-15 dBc (Max.)	@ +43 dBm Output
Spurious	-70 dBc (Max.)	@ +43 dBm Output
HPA Enable/Disable	TTL "Low or Open" ⇒ Enable TTL "High" ⇒ Disable	Pin 5
Switching On/Off Time @ 90% Power Output	3 μs (Max.)	TTL Control Signal: 1 KHz, 50% Duty Cycle
DC Input Voltage/Current	+28 VDC ± 2V / 3.2 A (Max.)	@ +43 dBm Output
Efficiency	> 24%	@ +43 dBm Output
Power Detect Range	25 dB (Min.)	
Temperature Sensor	Vt +500mV, 10mV/°C	Pin 3
Input / Output Impedance	50 Ω	
Input MAX. Signal (without Damage)	+15 dBm	
Load Conditions (No Damage)	6 : 1	

4. DB9 Pin Description		
1, 2	NC	
3	Temperature Sensor	
4	NC	
5	Enable/Disable	Enable: TTL Low or Open Disable: TTL High
6, 7	+ 28V	
8, 9	Ground	

5. Outline Drawing



2. Mechanical Characteristics		
Monitoring Connector	DB-9-Male	4 - 40 screw
RF IN/OUT Connector	SMA 4 Holes - Female	
DC Input	Pin 6,7 on DB-9	
Dimensions	6.4" x 3.40" x 1.07"	
Weight	1.2 lb	

3. Environment Characteristics (Designed to meet)		
Operating Temperature	-30°C ~ +75°C	Base Plate
Storage Temperature	-40°C ~ +95°C	
Cooling	External Heat-Sink	
Humidity (Non-condensing)	95% (Max.)	Designed to meet: IAW MIL-STD-810F
Operating Altitude	10,000 Feet	
Vibration and Shock	Vibration 6.06 gRMS	Designed to meet: IAW MIL-STD-810F

Revision History			
REV	Reason to Change	Date	Initialed by
	Production approved	05/19/16	Y.Z