



MA500/10/44SK-A is a broadband high power amplifier for VHF-UHF/Cellular/GSM applications. Amplifier supports signal amplification in the 20 ~ 1000 MHz frequency band and is protected against over-temperature and excessive current draw.

Model: MA500/10/44SK-A



1. Electrical Characteristics		
Item	Value	Note
Frequency Range	20 ~ 1000 MHz	
Gain	44 dB (Min.)	
Gain Flatness	±1.5 (Max.)	Over Frequency Range
VVA Range	25 dB (Min.)	
Output P1	+40 dBm (Min)	
Output Psat	+44 dBm (Min.)	
Output 3 rd Intercept Point	+48 dBm (Typ.)	2 CW tones, @ +27 dBm per tone, 100 kHz spacing
Input / Output VSWR	2:1 (Max.)	
Spurious	-60 dBc (Max.)	
Efficiency	16% (Min.)	Pout @ 25 Watts
Harmonics	-20 dBc (Typ.)	Pout @ 10 Watts
HPA Enable / Disable	TTL "0V or Open" ⇒ Enable TTL "5V" ⇒ Disable	
Temperature Sensor Output	10 mV / °C	
Current Sensor Output	275 mV / A	
HPA Switching ON/OFF Speed	2 μs	
DC Input Voltage	+26 to +28V	
Current Consumption	6.5 A (Max.)	@ 25 Watts Power Output
Input / Output Impedance	50 Ω	
Max. Input Signal (Without Damage)	+5 dBm	

2. Mechanical Characteristics		
Monitoring Connector	DB9-Male	4 – 40 screw
RF IN/OUT Connector	SMA 4 Holes – Female	
DC Input	Pin 6 and Pin 7 @ DB9	
Dimensions	6.4" x 3.4" x 1.06"	

3. Environment Characteristics		
Operating Temperature	-40°C ~ +70°C	Base Plate
Humidity Protection		*Lacquer on board

Revision History			
REV	Reason to Change	Date	Initialed by
	Released to production	11/09/12	YZ

4. DB9 Pin Description		
1	N/C	
2	Current Monitor	275 mV / A
3	Temperature Monitor	10 mV / °C
4	VVA Control	0-5V 0V: Gain Max. 5V: Gain Min.
5	Enable / Disable	0V or Open: Enable 5V: Disable
6, 7	+28 V	
8, 9	GND	

5. Outline Drawing

